

IMAGETEAM™ 3870

Cordless Linear Imager

Hand Held Products is pleased to introduce linear imaging technology in a cordless bar code reader. A bright, sharp aiming line and high-resolution imaging combine to deliver bar code reading performance that was previously only possible using a laser scanner.

The IMAGETEAM™ (IT)3870 offers many advantages over a laser scanner. Its aiming line is brighter than a standard laser. It scans and decodes 270 times per second, about seven times faster than a laser. It can read all common linear bar codes, plus PDF417 and MicroPDF417. Thanks to onboard Flash memory, the reader can be easily upgraded when new features and new symbologies become available.

The IT3870 joins a family of rugged and reliable cordless products, including the SCANTEAM® 2070 host interface base unit. The IT3870PDF is designed for aggressive reading performance on PDF417 and MicroPDF417. The IT3870HD reads high density bar codes with dimensions as small as 3 mil., while the IT3870LX reads 15 mil. codes out to 18 inches. All these configurations feature an IP 54 sealed-enclosure rating and the industry's best drop specification for cordless scanners.

The IT3870 cordless scanner addresses the needs of many applications. It is designed for tough industrial use, such as on loading docks, where shipping and receiving of materials requires the freedom to move around, and industry standards recommend the use of linear bar codes and PDF417 codes on shipping labels. The cordless scanner is also ideal for manufacturing applications, such as work-in-process, where safety may be an issue. Eliminating the cables prevents the cord from getting entangled in machinery and equipment, thus avoiding the chance of an accident. Other applications include interfacing to RF LAN based terminals mounted on forklift trucks, tool crib management, asset tracking, inventory control, and point-of-sale terminals.



Features & Benefits

Multiple Scanner Support

Each base unit supports up to nine scanners simultaneously. This increases productivity and flexibility without the added costs of additional bases and terminals.

Application Work Groups

Supports up to nine application work groups on a single base. This extremely powerful feature increases the number of jobs supported by a terminal, and allows you to easily adjust to changing workloads.

Broad Range Coverage

Scanner coverage of 7850 square feet (730 square meters) increases mobility and productivity by allowing the scanner to be taken to the job, rather than taking the job to the scanner.

Eliminates Cables

Improves safety conditions by avoiding accidents and injury as a result of cables becoming entangled in equipment and machinery. Eliminates cable replacement costs.

Unique Charge Pack Design

Removable charge pack that is recharged simply by plugging into a wall outlet, then operates through the entire work day.


Rugged Design

Water and dust resistant to IP 54 rating.

State-of-the-Art Radio Technology

Two-way 2.4 GHz frequency hopping spread spectrum radio with forward error correction is robust against interference. Makes use of the license-free ISM band. Robust system delivers reliable and snappy, error-free communication.

Typical reading zones on good quality bar codes measured in inches



Optical Performance

| | |
|------------------------------------|----------------------------|
| Illumination: | 630 nm Visible Red LED |
| Receiving Device: | 3648 element linear imager |
| Skew Angle: | +30° |
| Pitch Angle: | +15° |
| Horizontal Velocity: | 3 in. (7.6 cm) per second |
| Min. Reflective Difference: | 30% |
| Scan Rate: | 270 scans per second |

Mechanical/Electrical

Dimensions

| | |
|----------------|-------------------|
| Weight: | 16 oz. (448 g) |
| Height: | 8.5 in. (21.6 cm) |

Power Requirements

| | |
|-----------------------|---------------------------------|
| Input Voltage: | 4 to 14 VDC |
| Current Draw | |
| Operating: | 425 mA (typical) while scanning |
| Standby: | 30 mA |

Environmental

| | |
|--------------------------|----------------------------------------------|
| Sealing: | IP 54 (Water and Dust Resistant) |
| Temperature | |
| Operating: | 32° to 122°F (0° to 50°C) |
| Storage: | -22° to 140°F (-30° to 60°C) |
| Humidity: | 0 to 95%, non condensing |
| Mechanical Shock: | Functional after 26 drops from 6 ft. (1.8 m) |

Ambient Illumination: 0-100,000 lux

ESD Protection: Functional after 15 kV discharge

Radio

Frequency: 2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Spread Spectrum

Data Rates: 1 Mbps

Charge Pack: Nickel Metal Hydride (NiMH) battery

Input Voltage: 120 V/240 V, 50 Hz/60 Hz

Capacity: 1000 mAh

Number of Scans: 18,000

Expected Hours of Operation: 25 hours @ 1 scan every 5 seconds




Charge Time at 120 Vac: 6 hours for full charge from full discharge

Symbologies

Symbologies Supported: Codabar, Code 39, Code 128, ISBT 128, UPC/UPC-E, EAN/JAN, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 93, Code 11, ISBN, Telepen, and Reduced Space Symbology (RSS).
IT3870PDF: PDF417, MicroPDF417, and EAN•UCC Composite Symbology.

Warranty

Three year factory warranty



Agency Conformance

Consult your Hand Held Products' Customer Account Representative for specific country agency

| Electromagnetic Emissions/Immunity | Safety | RF Approvals |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| USA: FCC Part 15, Class B Canada: SOR 88/475 Class B Europe: EN 55022 (CISPR22) Class B, EN 61000-3-2 & -3, ETS 300 826 Other: EMC 89/336/EEC, EN 50082-1:1992, IEC 801-2:1991, IEC 801-3:1984, IEC 801-4:1988 | USA: UL listed, C22.2 No 950/UL 1950 Canada: cUL Listed Europe: TUV Rheinland GS Licensed EN 60950 (IEC950) Australia: AS/NZS 3548 | USA: FCC Part 15.249 Canada: RSS 210 Europe: ETS 300 328 |

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: (315) 685-8945
Fax: (315) 685-3172
Charlotte, NC
Tel: (704) 537-1444
Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
Tel: Int +31 (0) 40 24 24 486
Fax: Int +31 (0) 40 24 25 672
United Kingdom
Tel: Int +44 (0) 1 925 240055
Fax: Int +44 (0) 1 925 631280
France
Tel: Int +33 (0) 1 461 04111
Fax: Int +33 (0) 1 461 04120

Germany

Tel: Int +49 (0) 7 477 151377
Fax: Int +49 (0) 7 477 151378

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: Int +852 2511 3050/2511 3132
Fax: Int +852 2511 3557

Japan

Tel: Int +813 52127392
Fax: Int +813 32617372

Offices Serving Latin America

Naples, Florida
Tel: (941) 263-7600
Fax: (941) 263-9689